


SUBSTANCE	HYDRATED LIME
IDENTIFICATION	Free flowing, very fine white powder.
PROCESS/OR USE	Use as a constituent of mortar.
RISKS TO HEALTH	Irritating to eyes and skin. Risk of serious damage to eyes. May cause burns in the presence of moisture.



CAN THE EXPOSURE BE ELIMINATED **NO** Details specified below



FIRST AID MEASURES

EYES: Wash immediately with copious amounts of water.
 SKIN: Wash thoroughly with soapy water.
 INHALATION: Remove to fresh air.
 INGESTION: Wash mouth out with water and give milk to drink.

COPY MUST BE SENT WITH INJURED PARTY TO HOSPITAL



FIRE FIGHTING MEASURES (Tick Box)



SPILLAGE & ENVIRONMENTAL DETAILS

Wear correct PPE avoid skin and eye contact and avoid breathing in dust.
 Contained spilled product with sand or earth or other absorbent material.
 Prevent spills entering waterways and drains.
 Notify Environment Agency or other bodies if spills enter waterways or drains.



EXPOSURE LIMITS (EH 40)

Time Exposed: _____ Number of People Exposed: _____

Workplace Exposure Limit (WEL)

<i>Long Term Exposure Limit - 8 Hour TWA</i>	NA	ppm	Inhalable 10	mg.m ⁻³
			Respirable 4	
<i>Short Term Exposure Limit - 15 Minute</i>	NA	ppm	NA	mg.m ⁻³

PPE
(Tick Box)

<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

CONTROL MEASURES

Advise all persons involved in the use of hydrated lime on the inherent dangers of cement in the form of site start up briefing. Thorough site supervision to be maintained to ensure that PPE is worn without exemption.

Site Agent

